

IMPASOL® ANTISILIKON

Residue-free degreaser

Increases the adhesion of paints and varnishes

Excellent evaporation rate

High degreasing power

Removes silicone, antiseize and other heavy lubricants

Anti-corrosive

Compatible with most plastics

IMPASOL® ANTISILIKON is a special degreaser completely different from conventional hydrocarbons. It does not contain aromatic benzenes. It is applicable in all sectors of the **automotive, mechanical, electrical, packaging, agricultural and textile industries**. It removes dust, grease, wax, lubricants, oils and silicone perfectly and without residue. Due to its safe composition, it is also intended for degreasing machines and machine complexes in industry where it is not classified as a CMR substance (carcinogenic, mutagenic, reprotoxic).

IMPASOL® ANTISILIKON

- ✚ **High drying speed and residue-free evaporation (painting, varnishing)**
- ✚ **biodegradability (washing in the agricultural industry, degreasing of structures)**
- ✚ **ideal for quick evaporation degreasing before painting and gluing**
- ✚ **very strong solvent for most oils (including silicone), greases and petroleum jelly (including antiseize).**
- ✚ **Uniquely dissolves waxes and resins**

An effective multi-purpose cleaner for machinery, engines, metal surfaces and a powerful degreaser before bonding, painting, staining or other surface treatments (e.g. galvanizing). Gently and effectively removes grease and dirt from plastics, painted and varnished surfaces (must test for compatibility). Suitable for the packaging and processing industry.

CHARACTERISTICS	STANDARD	VALUE	UNIT
Test - Copper plate corrosion 100 h at 40°C	ASTM D 130	1	The Record
Physical condition and appearance	Visually	Fluid	transparent
KB index, solvent ability [rating]	ASTM D 1133	68	
Refractive index of light, at 20°C	ASTM D 1218	1,4350	
Density, at 15°C	ASTM D 4052	860-890	kg/m ³
Odour		mild	
Flash point in closed container	ISO 2719	-4	°C
Auto-ignition point	ASTM E 659	230	°C
Evaporation rate relative (ether=1)	DIN 53 170	22	
Viscosity at 20°C	ASTM D 445	0,8	mm ² /s
Evaporation rate		4 minuty	

Application:

We recommend a test before use. Remove all signs of loose corrosion and oxidation by osmosis or wire brush. Apply the product to the soiled surface and leave on. Use a stiff brush or stiff brush to agitate the deposited dirt. Always wipe off dissolved dirt with a clean cloth. Repeat the process for heavier soiling. The product can be used by hand or in degreasing baths.

PACKAGING: Canister 1l, 5l and 30L

STORAGE: Store out of reach of children and away from sources of ignition.

Read safety data sheets before use. The values given are averages and do not represent a specification.

HF SERVIS s.r.o., Plešnice 25, 330 33 Město Touškov, **Tel.: 377 279 255** www.impasol.com

E-mail: impasol@hfservis.cz