

IMPASOL[®] 6

COLD DEGREASER

**Instant substitution of Trichloro-1,1,1,-ethane,
Perchlorethylene, Acetone, petrol,
solvents organic
and benzine**

Non residue degreaser

BIODEGRADABLE

Non-flammable

Odourless product

Fast evaporation

High solvent power

Anticorrosive

Easily recycled

Compatible with most plastics

Very suitable for sedimentary dirtiness

IMPASOL[®] 6 is the mixture of synthetic chemicals absolutely different from classic hydrocarbon. It doesn't contain aromatic benzene.

IMPASOL[®] 6 is absolutely clear special basis odourless degreaser. It can be used in all industries - **engineering , electrical , light, agriculture and textile industry.**

IMPASOL[®] 6 can be used on all types of metals, plastics, rubber and elastomers. Due to its safe structure it is intended for degreasing of machines, machinery in industries and it is not classified as flammable product.

IMPASOL[®] 6 is intended to be used mainly for the applications where is needed:

- non flammable- no danger to work, to store and to handle the product
- fast caking (ideal to use in bathtubs)
- evaporation without residues (slower evaporation but after the surface is completely dry)
- it doesn't damage the surfaces of the materials (doesn't damage even the expanded polystyrene)
- primary anticorrosive protection of the materials (corrosive test on CU metal plate ASTM D 130-1) (takedown application, stocking, washing and degreasing)
- biodegradable (OECD 301F - 70%/ 28 dales) (washing in agriculture, degreasing of constructions)
- ideal for washing of electric motors and components (it drives out the water), which are not alive
- almost odourless (closed areas where it is not possible to ensure ventilation)

IMPASOL[®] 6 can be used in many production, maintenance and servis areas where it is not possible to use classic hydrocarbons, solvents organic, it doesn't worsen working conditions.

IMPASOL® 6

- high solvent power on most oils
- high solvent power on most fats and greases
- strong remover of carbonized materials
- solves very good waxes, epoxy resins and tar
- for manual application (swab, sponge and brush)
- for washing in washing machines, washers and tanks (it has low density - cause dirt and grease sink to the bottom of a tank - the lifetime of the product is longer)

Effective multipurpose cleaner of machinery, motors and all the engine compartment of automobile. Gently and affectively removes the greases and dirt from plastics, painted and laquered surfaces. The cleaner contains components which make protective film on cleaned metal surfaces so such surfaces are protected against rust and also water is repelled for a short time. It removes asphalt spots from varnished surfaces. This product is ideal to degrease surfaces before storage It is suitable for manufacturing industry. It protects the rubber parts, it cleans and protects plastics and electrocontacts against moisture.

Characteristics	Norm	Rate	Set
Appearance	visually	Transparent	
Test - Cu plate 100 h v 40°C	ASTM D 130	1	Record
Colour SAYBOLT	ASTM D 156	30	NF M 07003
Physical condition	visually	liquid	
Initial point	ASTM D 86, NF M 07 002	175	°C
Terminal point		210	°C
Index KB, solvent capability	ASTM D 1133	31	
Index refraction 20°C	ASTM D 1218	1,4350	
Solubility - Hildebrand		7,6	
Density - 15°C	ASTM D 4052	780-810	kg/m ³
Odour		Without odour	
Flash point, closed up	ISO 2719	62	°C
Spontaneous combustion point	ASTM E 659	230	°C
Aromatics content	TS IL 13 (UV)	0,03	% v/v
Benzene content	ASTM D 4367	Max. 1	ppm
Sulphur content	ASTM D 5453	Max. 1	ppm
Aniline point (automatically)	ASTM D611	73	°C
Evaporating rate (ether=1)	DIN 53 170	200	
Steam pressure (tension) 20°C	NF M 07 007, ASTM D 323	<1	mbar
Steam pressure (tension) 37,8°C		<3	mbar
Bromine Index	ASTM 2710	10	mgBr/100g
Viscosity a` 20°C	ASTM D 445	1,7	mm ² /s
Evaporating velocity		60 minut	

APPLICATION METHOD:

Impasol 6 - Clear degreaser suitable for all types of materials. It is recommended to be tested before use and to remove all the marks of corrosion and oxidation by sand paper or wire brush. Pile up on dirty surface and leave it to function. Dissolved dirtiness can be wiped out, the best effect can be obtained by rinsing off with water. The effect can be better if wire brush or sand paper is used before the application to stir the dirtiness. This way the product can get easier to the surface. If the pollution is high the procedure can be repeated. It can be used manually or in degreasing tanks.

Packaging: 20l tank, 120l (6* 20l tanks), 200l drum

Shelf life: Stock out of reach of children and of the ignition source.

The values are average and do not represent the specification.

HF SERVIS s.r.o., Plešnice 25, 330 33 Město Touškov

Tel. : 377 279 255, E-mail: technik@hfservis.cz www.hfservis.cz

www.impasol.com