

IMPACLEAN AQUA B 205

INDUSTRIAL EXTRA STRONG CLEANER FOR SPRAYING, GANTRY AND HIGH PRESSURE EQUIPMENT

It is a low foaming, biodegradable, surface friendly cleaning concentrate designed for use in the engineering and automotive industries for cleaning machines, engines, products, structures, chassis, bodies, car bodies, moulds, dies, work surfaces, floors, walls and tools of oils, grease and dirt. **Ideal for washing machinery and products after machining, welding, finishing and technical services.**

Cleans dirt, mineral and synthetic fats and oils, waxes from all water washable hard surfaces (tiles, metals, stainless steel, glass, tiles, enamel surfaces). Replaces flammable, toxic, chlorinated hydrocarbons such as gasoline, thinners, flammable degreasers. Can be used on all water-resistant surfaces.

Routine cleaning of walls, floors, machinery and equipment, windows, fittings, work surfaces, signs, vehicles, etc. (any hard surfaces). Removes dirt and grime from masonry, glazed tiles, stone, marble and concrete. Does not damage seals, NBR and silicone "O" rings, rubber and most plastics.

- ✚ **Extra strong cleaner of biological impurities**
- ✚ **Extra strong cleaner of mineral and synthetic oils**
- ✚ **Extra strong cleaner of mineral and synthetic lubricants**
- ✚ **Powerful cleaner of animal and vegetable fats and oils**
- ✚ **Removes even silicone petroleum jelly and oil**
- ✚ **Low foaming**
- ✚ **High content of active ingredients**
- ✚ **Does not damage surfaces**

Application

Routine cleaning of walls, floors, machinery and equipment, windows, machine parts and tools, moulds, work surfaces, signs, skeletons, etc. (any hard surfaces). Removes dirt and grime from metals, plastics, glass, masonry, glazed ceramics, stone, marble and concrete parts.

■ **Cleaning in the engineering industry**

Today's surfaces (paints and varnishes, glass, plastics, metals and coloured and other materials) are very expensive. B 205 is safe - it will not damage aluminum, iron, cast iron, brass, bronze, copper, glass, ceramics, concrete, painted surfaces and most plastics. By using this product you will significantly reduce your washing costs. B 204 can be used for indoor and outdoor purposes.

Application to

Animal fats and oils	Vegetable fats and oils	Mineral fats and oils	Synthetic fats and oils	Frequency washing	Settled dirt	Waxes
◆◆◆	◆◆◆	◆◆◆	◆◆	◆◆◆	◆◆	◆◆◆

Method of application

Wiping	Painting	Soaking	Spraying	High-pressure spraying	By Machine
◆◆	◆◆	◆◆	◆◆◆◆	◆◆◆◆◆	◆◆◆

Diluting

Engines, chassis	Machines	Skeletons, forms	Work surfaces, tools
1:100	1:300	1:400	1:500

Technical table

Product	PH	Colour	Base	Appearance	Flash point
B 205	11-12	Transparent	Tenside, water	Viscous liquid	NOT

Application B 205 :

The product is a concentrate, set the device or dilute 1:100 to 500 with clean warm water (+60°C). For large layers of mineral deposits, first wash thoroughly with Impaclean Aqua C310 and rinse with clean water, then use B205.

Spray application: hand-held applicators, low pressure and high pressure spraying

Consumption: is 10-20m² of 1L diluted product according to the surface structure.

Apply to surface, leave on for 5 to 10 minutes, we can use a brush, this will greatly increase the efficiency. **After cleaning, rinse thoroughly with clean water, preferably under high pressure. Do not let dry.**

In case of heavy contamination, increase the concentration or leave it on longer. Using pressure equipment equipped with a foam tip, it produces a foam for washing vertical surfaces that removes dirt very effectively. For manual applications we recommend the EPOCA 2000 applicator. Always rinse with clean water after cleaning.

Due to the wide range of surfaces, we recommend to perform a Surface Compatibility TEST before the actual application.

These values are averages and do not represent a specification. Read safety data sheets before use!

HF SERVIS s.r.o.
330 33 Plešnice 25

Czech republic

Tel. : +420 377 279 255

impasol@hfservis.cz

www.hfservis.cz

HFSERVIS

WWW.IMPASOL.COM